

Industrija za elektricni greaci, gumeni proizvodi i servis

## **CARLITOS 2600 FUNCTIONAL CHARACTERISTICS:**









Modular backless bench for use in transit areas of passenger terminals (airports, train stations, etc.) and in areas of short haul waiting time (museums, bank offices, etc.).



Ovoj criez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva ,umnozuva niti kopira bez soglasnost od Elrotrol

vo sprotívno se snosat posledici vo smislana clenovite 163 i 164 od krivicniot zakon R.M. (povreda na avtorsko pravo)

Elektroluks is registered trademark of Elektrouks companies in Macedonia and other countries

Industrija za elektricni greaci, gumeni proizvodi i servis

The bench unit is formed by two joined aluminium profiles that provide the structure and act as the seat surface. Pedestals are used as an element to join the two profiles. All components are made of aluminium; no welds are used in the entire unit, which prevents any possible oxidation and ensures ease of maintenance. Given its characteristics, this model can be both for outdoor and indoor use.

#### MOD. 2600

bez soglasnost od Elrctroli

criez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva ,umnozuva niti kopira

This is the most basic version. The bench consists of a continuous profile with no upholstery or arms, with a capacity of 4/5 places, and with only two pedestals. Benches of greater length are specified on a project basis. The standard paint finish used is RAL 9007TX.

#### MOD. 2600-TZ

vo sprotívno se snosat posledici vo smislana clenovite 163 i 164 od krivicniot zakon R.M. (povreda na avtorsko pravo) 64 The seat incorporates polyurethane foam padding protected with the TS System fire barrier and vinyl covering. This finish enhances a high level of resistance and durability to heavy-duty use while, at the same time, is easy to clean and maintain. This model can also be upholstered in natural leather.

#### MOD. 2600-TZ-BR

This model has the same characteristics as the 2600-TZ, but incorporates intermediate arms. These arms are made entirely of aluminium and are upholstered on their upper part. The upholstery has the same characteristics as that used for the seat.

45 16.9



Elektroluks is registered trademark of

in Macedonia and

Elektrouks companies

45 17.7" bez soglasnost od Elrctrolu

critez e sopstvenost na Electralux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva ,umnozuva niti kopira

vo sprotívno se snosat posledíci vo smislana clenovite 163 i 164 od krivicniot zakon R.M. (povreda na avtorsko pravo)

265 104.3"

> 65 25.6"

# TECHNICAL CHARACTERISTICS:

## **ALUMINIUM:**

Material: UNE L-2630
Density: 2.7 gr/cm<sup>3</sup>

• Breaking load: 20 kg/mm<sup>2</sup>

## POLYURETHANE:

Density: 40 kg/m<sup>3</sup>

 Self-extinguishing: UNE 23727 NF/P 92307

## PAINT:

Electrostatic epoxy powder

Coat thickness: 70-80 microns

Grid adherence: 100%

Elektroluks is registered trademark of Elektrouks companies in Macedonia and other countries



000





Industrija za elektricni greaci, gumeni proizvodi i servis

#### **UPHOLSTERY:**

- Vinyl fabric: DIN 75200, DIN 53438, NVSS 302, BS 5852 crib 5, BS 7176 28 N/m<sup>2</sup>
- Impact strength DIN 53453 no break

## FIRE BEHAVIOUR STANDARDS:

**United Kingdom:** 

BS 5852. Section 5. Ignition sources 0, 1 and 5

Germany:

DIN 54342, part 1 and 2

Italy:

critez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva "umnozuva niti kapira bez soglasnost od Elratrol

CSE RF/4/83 class 1. IM

Spain/France:

UNE 23727/NF 92-503



